

# XSPlug® P3

## 1.8 HSDPA USB Connector

### Features

- Mobile internet access at DSL speed
- Connection and power supply via USB interface
- Up to 1.8 MB/s in 3G mobile networks (HSDPA/UMTS)
- Up to 237 KB/s in 2G mobile networks (EDGE/GPRS/GSM)
- SMS functions (send, receive, forward, store)
- Updateable due to Flash Memory technology

### Compatibility

- For all laptops and PCs with USB interface
- Compatible with Windows™ and Apple™ operating systems
- Suitable for safe connections via IPsec and VPN

### Highlights

- Mobile internet with USB interface
- Up to 1.8 MB/s downlink per HSDPA
- For Windows™ and Apple™ computers
- Power supply via USB interface
- Maximum usability

## Mobile Highspeed Surfing via USB

The **XSPlug® P3** offers internet access at DSL speed via the mobile net. PCs and laptops are connected via their USB interface, which at the same time allows the power supply of the device. All software installation is done automatically.

The **XSPlug® P3** is the ideal solution for those who require access to data and applications at home as well as on the move. Get mobile into internet and intranet with your laptop or PC – even via IPsec and VPN secured connections.

The **XSPlug® P3** offers a downlink speed up to 1.8 MB/s in the HSDPA mobile net. Without HSDPA it achieves up to 384 KB/s in 3G nets via UMTS. In 2G nets this PC card secures worldwide data access via EDGE (up to 237 KB/s) and GPRS.



**4G**  
SYSTEMS

the  
convergence  
company

# XSPlug<sup>®</sup> P3

## 1.8 HSDPA USB Connector

### Specifications\*

<b>Frequency bands</b>	UMTS (WCDMA FDD): 2100 MHz (EMEA) EDGE: 850/900/1800/1900 MHz GSM/GPRS: 850/900/1800/1900 MHz
<b>Data rates</b>	HSDPA: up to 1.8 MB/s DL and 384 KB/s UL UMTS: up to 384 KB/s DL and UL EDGE: up to 237 KB/s DL and 118 KB/s UL GPRS: up to 85,6 KB/s DL and 42,8 KB/s UL
<b>Antenna</b>	UMTS/GSM internal, frequency range 850 to 2100 MHz
<b>Administration</b>	Connect/disconnect button
<b>Update ability</b>	Firmware update per software upload
<b>Compatibility</b>	For all laptops and PCs with USB interface (1.1/2.0) Operating systems: Windows™ XP und 2000, MAC OS X
<b>Connectors</b>	Antenna: external (UMTS/GSM)
<b>Network connection</b>	IPSec and VPN compatible Always on, network re-connect
<b>Short Message Service</b>	Send/receive/transfer/store
<b>Operating conditions</b>	Working temperature: 0 to 50 degree Celsius
<b>Case</b>	Measurements (W/D/H): 60 x 11,8 x 113,5 mm Weight: 60 g
<b>Status indicators</b>	Connection status (LED)
<b>SIM card interface</b>	Card reader, SIM and USIM compatible
<b>Supported norms</b>	Europe CE GCF Type Approval FCC Type Approval PTCRB Type Approval
<b>Scope of delivery</b>	HSDPA USB connector User manual on CD-ROM Quick start guide

\* Subject to change without notice

**Contact** 4G Systems GmbH, Goldbekplatz 3, D-22303 Hamburg  
**Phone** +49 (0)40-70 38 33-0 **Fax** +49 (0)40-70 38 33-700  
**E-mail** sales@4g-systems.com **Internet** www.4g-systems.com



the  
convergence  
company