



Phonecell® SX7P

SX7P Fixed Cellular Phone



- Short Message Service (SMS)*
- Large LCD Display (optional)**
- Supports Polyphonic Ringtones

-
- ✓ Utilizes network features such as caller ID, call waiting/call hold, call forwarding
 - ✓ Hands-free speakerphone
-

This feature rich wireless phone is the perfect affordable solution for wireless local loop (WLL) deployments anywhere.

Models

- Dual Band 850/1900 GSM Phase 2+
- Dual Band 900/1800 GSM Phase 2+

* Subject to network availability.

** Shown with optional large LCD display

Phonecell® SX7P

Fixed Cellular Phone



Features

<u>Feature</u>	<u>200 Series</u>	<u>300 Series</u>
Backlit Keypad	Optional	Yes
Wallpaper	Optional	Yes
Large Display	Optional	Optional
FM Radio	Optional	Optional
Predictive Text Entry	Optional	Optional
Downloadable Ring tones	Optional	Optional
Backlit Display	Yes	Yes
Polyphonic Ringer	Yes	Yes
Special Character Languages	Yes	Yes
Circuit Switched Data	No	Yes
GPRS Data	No	Yes
PC Fax	Yes	Yes
Data Interface	No	Yes
Phonebook Size	100 (min)	500 (max)
Tone Profiles	Yes	Yes
SMS Group Message	Yes	Yes
Animated Icons	No	Yes
Full duplex Speakerphone	Yes	Yes
Call Log	Yes	Yes
Caller ID	Yes	Yes
FWP Lock	Yes	Yes
Alarm Settings	Yes	Yes
Handset/Network Call Barring	Yes	Yes
Speed Dialing	Yes	Yes
Audio Settings	Yes	Yes
Adjust Alert tones in profiles	Yes	Yes
Time & Date Settings	Yes	Yes
Voicemail & Text message alert	Yes	Yes
Call Settings	Yes	Yes
MO / MT SMS Text Messaging	Yes	Yes
ME Personalization	Yes	Yes
Minute Minder	Yes	Yes
Auto SIM PIN Entry	Yes	Yes
Auto Send Delay	Yes	Yes
Area Code Prefix	Yes	Yes
Automatic Call Disconnect	Yes	Yes
Fixed Dialing Number	Yes	Yes
Hotline	Yes	Yes
Hot Message Key	Yes	Yes
Calculator	Yes	Yes
Calendar	Yes	Yes
Games	Yes	Yes
Cell Lock	Yes	Yes

Specifications

Air Interface Standard

- GSM Phase 2+

Transmit Power

- GSM 850/900: 2 watts
- GSM 1800/1900: 1 watt

Frequency Ranges

	<u>Transmit</u>	<u>Receive</u>
• GSM 850	824-849 MHz	869-894 MHz
• GSM 900	890-915 MHz	935-960 MHz
• GSM 1800	1710-1785 MHz	1805-1880 MHz
• GSM 1900	1850-1910 MHz	1930-1990 MHz

FWT Dimensions and Weight

- Metric (cm) 165 L x 170 W x 65 H
- Weight (TBD)

Environment

- Operating temperature range: -20°C to +60°C
- Storage temperature range: -40°C to + 80°C
- Humidity: 5% to 95%

Connectors

- External antenna connector
- 2.5 mm headset jack
- USB power input jack

Antenna

- High performance internal antenna
- Optional external high gain antenna available

AC-to-DC Switching Power Supply (Included)

- Voltage: 110 V/230 VAC
- Frequency: 50/60 Hz
- Plug options: U.S., U.K., Euro, India

Internal Battery Backup(Optional)

- 3.6 V rechargeable battery pack.

Language Options

- English / Hindi
- English / Portuguese / French /Spanish

Telular Corporation • Corporate Headquarters • 647 North Lakeview Parkway • Vernon Hills, Illinois 60061 USA

Phone: 847-247-9400 • Fax: 847-247-0021 • E-mail: sales@telular.com • http://www.telular.com

Europe/Middle East/Africa • Phone: +44-1189-232-660 • uk@telular.com

Latin America • Phone: +1-954-217-0522 • miami@telular.com

Asia/Pacific • Phone: +65-735-7728 • singapore@telular.com